

Untergrundvorbereitung

Untergründe (beispielsweise)	Gussasphalt nach DIN EN 13813 (AS)	Zementestrich nach DIN EN 13813 (CT)	Calciumsulfat- oder Calciumsulfatfließestrich nach DIN EN 13813(CA/CAF)	Trockenestriche
Grundierungen (beispielsweise)	Sikafloor®-02 Primer (Entfällt bei ausreichender Absandung) Sika® Primer MB Rapid (Weichmachersperre bei Direktverklebung)	Sika® Level-01 Primer		
Spachtelmassen (beispielsweise)	Sikafloor®-300 Rapid Level			

Belagsverklebung

Belag/ Kollektion	Klebstoff	Auftragsgerät/ Zahnung gem. TKB	ca. Verbrauch/m²	Bemerkungen
Parkett				Einsatzbereich
3- Schichtparkett	SikaBond®-151 Elastischer Parkettklebstoff	TKB B11	ca. 1050 g/m²	
	SikaBond®-54 Parquet Leicht auftragbarer, elastischer Parkettklebstoff	TKB B11	ca. 800 g/m²	auch für 2-Schichtparkett / Massivholzdielen geeignet sowie problematische Holzarten
Designbeläge				
Vinyl Pro 2,5 mm Dryback-Sheet	SikaBond®-130 Design Floor Faserverstärkter Bodenbelagsklebstoff für Bodenbeläge	TKB A1	ca. 250 - 350 g/m²	
	SCHÖNOX® PROTECT Sicherheitsklebstoff für höchste Belastungen	TKB A1	ca. 250 - 350 g/m²	für Feuchträume geeignet
Vinyl Perform 6 mm Multilayer Rigid und Kork- Gegenzug	SikaBond®-151 Elastischer Parkettklebstoff	TKB B6	ca. 850 g/m²	für Feuchträume geeignet
HDC Dryback 2,5mm	SikaBond®-130 Design Floor Faserverstärkter Bodenbelagsklebstoff für Bodenbeläge	TKB A2	300 g/m²	
	SCHÖNOX® PROTECT Sicherheitsklebstoff für höchste Belastungen	TKB A1	360 g/m²	für Feuchträume geeignet
Designboden 3.0				
Dureco 12 mm	SikaBond®-151 Elastischer Parkettklebstoff	TKB B6	ca. 850 g/m²	
	SikaBond®-54 Parquet Leicht auftragbarer, elastischer Parkettklebstoff	TKB B6	ca. 650 g/m²	

Belag/ Kollektion	Klebstoff	Auftragsgerät/ Zahnung gem. TKB	ca. Verbrauch/m²	Bemerkungen
Echtholzboden				
Hywood Echtholz-Hybridboden Landhausdielen	SikaBond®-151 Elastischer Parkettklebstoff	TKB B11	ca. 800 g/m²	
	SikaBond®-54 Parquet Leicht auftragbarer, elastischer Parkettklebstoff	TKB B11	ca. 800 g/m²	

Renigung

Zubehör				
	Sika® PowerClean Feuchte Reinigungstücher			zum Entfernen von Klebstoffresten (im nicht ausgehärteten Zustand)

Soweit nicht anders angegeben, erfüllen alle Klebstoffe die Anforderungen EC1 PLUS gem. GEV.

Bitte beachten Sie die technischen Informationen unserer Produktdatenblätter, die Verlegehinweise des Belagsherstellers, die einschlägigen Vorschriften, Richtlinien und Merkblätter. Im Zweifel empfehlen wir einen Praxisversuch und/oder die Rücksprache mit dem Sika Produktservice Tel. 02547/910-325. Weitere Informationen erhalten Sie im Internet unter www.sika.de oder unter www.terhuerne.de

I Sika ADHESIVE RECOMMENDATION - ter Hürne



Substrate preparation

Substrates (for example)	Mastic asphalt according to DIN EN 13813 (AS)	Cement screed according to DIN EN 13813 (CT)	Calcium sulphate levelling screed or calcium sulphate flowing screed in accordance with DIN EN 13813(CA/CAF)	Dry screeds
Primers (for example)	Sikafloor® -02 Primer (Not applicable with sufficient sanding)	Sika® Level-01 Primer		
	Sika® Primer MB Rapid (plasticiser barrier for direct bonding)			
Levelling compounds (for example)	Sikafloor® -300 Rapid Level			

Covering bonding

Covering/ Collection	Adhesive	Applicator/ tothing according to TKB	approx. consumption/m²	Remarks
Parquet flooring				Field of application
3-layer parquet	SikaBond®-151 Elastic parquet adhesive	TKB B11	approx. 1050 g/m²	
	SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive	TKB B11	approx. 800 g/m²	Also suitable for 2-layer parquet / solid wood planks and problematic types of wood
Design coverings				
Vinyl Pro 2.5 mm dryback sheet	SikaBond®-130 Design Floor Fibre-reinforced floor covering adhesive for floor coverings	TKB A1	approx. 250 - 350 g/m²	
	SCHÖNOX® PROTECT Safety adhesive for the highest loads	TKB A1	approx. 250 - 350 g/m²	Suitable for damp rooms
Vinyl Perform 6 mm multilayer rigid and cork backing	SikaBond®-151 Elastic parquet adhesive	TKB B6	approx. 850 g/m²	Suitable for damp rooms
HDC Dryback 2.5mm	SikaBond®-130 Design Floor Fibre-reinforced floor covering adhesive for floor coverings	TKB A2	300 g/m²	
	SCHÖNOX® PROTECT Safety adhesive for the highest loads	TKB A1	360 g/m²	Suitable for damp rooms
Design floor 3.0				
	SikaBond®-151 Elastic parquet adhesive	TKB B6	approx. 850 g/m²	

Dureco 12 mm	SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive	TKB B6	approx. 650 g/m²	
-----------------	--	--------	------------------	--

1

26.04.2023

BUILDING TRUST



I Sika ADHESIVE RECOMMENDATION - ter Hürne

Covering/ Collection	Adhesive	Applicator/ toothings according to TKB	approx. consumption/m²	Remarks
Real wood floor				
Hywood real wood hybrid flooring wideplank	SikaBond®-151 Elastic parquet adhesive	TKB B11	approx. 800 g/m²	
	SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive	TKB B11	approx. 800 g/m²	

Cleaning

Accessories				
	Sika® PowerClean Moist Cleaning Wipes			for removing adhesive residues (in the uncured state)

Unless otherwise stated, all adhesives fulfil the requirements EC1 PLUS according to GEV.

Please observe the technical information in our product data sheets, the installation instructions of the flooring manufacturer, the relevant regulations, guidelines and data sheets. In case of doubt, we recommend a practical test and/or consultation with Sika Product Service Tel. 02547/910-325. Further information is available on the Internet at www.sika.de or at www.terhuerne.de

