

















Product details		Laminate Floor		
Dimension:		1285 x 192 x 7 mm	1285 x 192 x 8 mm	1288 x 195 x 8 mm
Groove:		without joint / V-groove 4-sided (4V)	without joint	V-groove 4-sided (4V)
Profile:		ClickTec	ClickTec	SmartConnect
packaging	package:	10 pieces per pack (ca. 2,467 m ²)	9 pieces per pack (ca. 2,22 m ²)	9 pieces per pack (ca. 2,26 m ²)
	pallet:	40 packs per pallet (ca. 98,68 m ²)	40 packs per pallet (ca. 88,8 m ²)	52 packs per pallet (ca. 117,52 m ²)
Weight	package:	ca. 14,8 kg	ca. 15,5 kg	ca. 15,0 kg
	pallet:	ca. 607,2 kg	ca. 635 kg	ca. 820 kg
tolerances: requirements EN 13329				
Flatness of element, f [%]	≤ 0,50 / ≤ 1,00 (lengthwise) ≤ 0,15 / ≤ 0,20 (wide)	Gap opening between elements, o [mm]		≤ 0,15 (average) ≤ 0,20 (single value)
High difference between elements, h [mm]	≤ 0,10 (average) ≤ 0,15 (single value)	Thickness of the elements, t [mm]		≤ 0,50
Squareness, q [mm]	≤ 0,20	Length of the surface layer, l [mm]		± 0,50 mm
Straightness, s [mm/m]	≤ 0,30	Width of the surface layer, w [mm]		± 0,10 mm (average) ≤ 0,20 mm (single value)
Decor deviation [mm]	± 2 mm			
Product construction				
 <ul style="list-style-type: none"> 1) Protective top layer 2) Decor layer 3) Baseboard 4) Backing Layer 				
Warranty (according to our separate terms of warranty)	15 years for domestic use	Note		
      				
product properties				
		test standard	evaluation	
	Usage class Heavy domestic use	EN 13329	23	
	Usage class Moderate commercial use	EN 13329	31 valid for 7 mm thickness	
	Usage class Moderate commercial use	EN 13329	32 valid for 8 mm thickness	
	Abrasion resistance	EN 13329	IP ≥ 2000 turns (AC 3) for 7 mm thickness IP ≥ 4000 turns (AC 4) for 8 mm thickness	
	Reaction to fire	EN 13501-1	C(f) s1 flame retardant	
	Formaldehyde	EN 16516	E1	
	Light fastness	EN 13329	Blue wool scale ≥ 6 Grey scale ≥ 4	
	Slide resistance	EN 13893	The requirements are in compliance with DIN EN 14041 (my ≥ 0,3)	
	Elektrostatic behaviour	EN 1815	not antistatic	
	Imprint after constant loading	EN 13329	≤ 0,05 mm	
	Resistance to chair castors	EN 13329	no visible changes or impact as defined by (Typ W) EN 425:2002	
	Thermal resistance	EN 12667	0,062 (m ² K)/W ± 15%	
	Underfloor heating- hot water and electrical	EN 1264-2	Suitable with a maximum surface temperature of 27°. Electric panel heating with soft heating technology and temperature control unit are suitable as well.	
	Stain resistance	EN 13329	Group 1 + 2 = degree 5 Group 3 = degree 4	
	Impact stress resistance	EN 13329	small ball ≥ 10 mm · big ball ≥ 500 mm for 7 mm thickness small ball ≥ 35 mm · big ball ≥ 750 mm for 8 mm thickness	
changed by:	ter Hürne	date:	Aug. 23	update