

## Substrate preparation

Substrates (for example)	Mastic asphalt according to DIN EN 13813 (AS)	Cement screed according to DIN EN 13813 (CT)	Calcium sulphate or Calcium sulphate flowing screed according to DIN EN 13813(CA/CAF)	Dry screeds
Primers (for example)	SCHÖNOX SHP (Not applicable with sufficient sanding)  SCHÖNOX® HP RAPID (plasticiser barrier for direct bonding)	SCHÖNOX VD		
Levelling compounds (for example)	SCHÖNOX HS 10 SCHÖNOX HS 10 F SCHÖNOX HS 50			SCHÖNOX HS 10

## Covering bonding

Covering/ Collection	Adhesive	Applicator/ Toothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
<b>Multi-layer parquet</b>				Field of application
<b>Parkett Friends Naturholz Parkett</b>	<b>SCHÖNOX® PARKETT 260</b> Wasserfreier Spezialklebstoff für Parkett	TKB B11	ca. 1050 g/m <sup>2</sup>	
	<b>SCHÖNOX® iLINE® 250</b> Schub-elastischer Parkettklebstoff	iLINE APP	ca. 800 g/m <sup>2</sup>	
	<b>SCHÖNOX® PARKETT 410</b> Wasserfreier Klebstoff für Parkett	TKB B11	ca. 1000 g/m <sup>2</sup>	
<b>Real wood hybrid flooring</b>				
<b>Hywood Landhausdiele, Schlossdiele, Fischgrät</b>	<b>SCHÖNOX® PARKETT 260</b> Wasserfreier Spezialklebstoff für Parkett	TKB B11	ca. 1050 g/m <sup>2</sup>	
	<b>SCHÖNOX® PARKETT 54</b> Verbrauchsoptimierter, elastischer, wasserfreier Spezialklebstoff für Parkett	TKB B11	ca. 800 g/m <sup>2</sup>	
<b>Design vinyl flooring</b>				
<b>Vinyl Friends Dryback Soya Design Vinylboden Pro</b>	<b>SCHÖNOX® DUROCOLL</b> Faserverstärkter Einseit Dispersionsklebstoff	TKB A1	ca. 250 g/m <sup>2</sup>	
	<b>SCHÖNOX® PROTECT</b> Sicherheitsklebstoff für höchste Belastungen	TKB A1	ca. 360 g/m <sup>2</sup>	including critical substrates, e.g. damp rooms and areas with strong sunlight / temperature exposure
	<b>SCHÖNOX® PU 900</b> Zweikomponenten- Polyurethanklebstoff	TKB A2	ca. 500 g/m <sup>2</sup>	including critical substrates, e.g. damp rooms and areas with strong sunlight / temperature exposure

Covering/ Collection	Adhesive	Applicator/ Toothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
Pro Soya Designboden Perform	SCHÖNOX® PARKETT 260 Wasserfreier Spezialklebstoff für Parkett	TKB B6	ca. 250 - 350 g/m <sup>2</sup>	leveled subfloor
	SCHÖNOX® iLINE® 250 Schub-elastischer Parkettklebstoff	iLINE APP	ca. 800 g/m <sup>2</sup>	leveled subfloor
<b>Dureco-Boden</b>				
Dureco strong	SCHÖNOX® PARKETT 260 Wasserfreier Spezialklebstoff für Parkett	TKB B6	ca. 850 g/m <sup>2</sup>	
	SCHÖNOX® PARKETT 54 Verbrauchsoptimierter, elastischer, wasserfreier Spezialklebstoff für Parkett	TKB B6	ca. 650 g/m <sup>2</sup>	
<b>PVC free design floor</b>				
Avatara Designboden Pro	SCHÖNOX® EMICLASSIC ® Universal - Dispersionsklebstoff	TKB A2	ca. 280 g/m <sup>2</sup>	
	SCHÖNOX® PROTECT Sicherheitsklebstoff für höchste Belastungen	TKB A1	ca. 360 g/m <sup>2</sup>	including critical substrates, e.g. damp rooms and areas with strong sunlight / temperature exposure
<b>Akustic panel</b>				
SilentDesign	SCHÖNOX SLK		ca. 2 Kartuschen pro Platte	Wall bonding only, screws must be used in the ceiling area.
<b>Skirting boards</b>				
Wood-based material	SCHÖNOX SLK		ca. 44ml pro/m	

Accessories				
	<b>SCHÖNOX® FIX CLEAN</b> <b>Feuchte Zellstoff-Reinigungstücher</b>			For easy removal of adhesive residues. Especially for contamination with uncured adhesive residues.

Unless otherwise stated, all adhesives fulfil the requirements EC1 PLUS according to GEV.

Please observe the technical information in our product data sheets, the installation instructions of the flooring manufacturer, the relevant regulations, guidelines and data sheets. In case of doubt, we recommend a practical test and/or contact Sika Product Service on 02547/910-325. Further information is available on the Internet at [www.sika.de](http://www.sika.de) or at [www.terhuerne.de](http://www.terhuerne.de)