

# I Sika ADHESIVE RECOMMENDATION - ter Hürne



## Substrate preparation

Substrates (for example)	Mastic asphalt according to DIN EN 13813 (AS)	Cement screed according to DIN EN 13813 (CT)	Calcium sulphate levelling screed or calcium sulphate flowing screed in accordance with DIN EN 13813(CA/CAF)	Dry screeds
Primers (for example)	Sikafloor® -02 Primer (Not applicable with sufficient sanding)  Sika® Primer MB Rapid (plasticiser barrier for direct bonding)	Sika® Level-01 Primer		
Levelling compounds (for example)	Sikafloor® -300 Rapid Level			

## Covering bonding

Covering/ Collection	Adhesive	Applicator/ tothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
<b>Parquet flooring</b>				Field of application
<b>3-layer parquet</b>	<b>SikaBond®-151 Elastic parquet adhesive</b>	TKB B11	approx. 1050 g/m <sup>2</sup>	
	<b>SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive</b>	TKB B11	approx. 800 g/m <sup>2</sup>	Also suitable for 2-layer parquet / solid wood planks and problematic types of wood
<b>Design coverings</b>				
<b>Vinyl Pro</b> 2.5 mm dryback sheet	<b>SikaBond®-130 Design Floor Fibre-reinforced floor covering adhesive for floor coverings</b>	TKB A1	approx. 250 - 350 g/m <sup>2</sup>	
	<b>SCHÖNOX® PROTECT Safety adhesive for the highest loads</b>	TKB A1	approx. 250 - 350 g/m <sup>2</sup>	Suitable for damp rooms
<b>Vinyl Perform</b> 6 mm multilayer rigid and cork backing	<b>SikaBond®-151 Elastic parquet adhesive</b>	TKB B6	approx. 850 g/m <sup>2</sup>	Suitable for damp rooms
<b>HDC Dryback 2.5mm</b>	<b>SikaBond®-130 Design Floor Fibre-reinforced floor covering adhesive for floor coverings</b>	TKB A2	300 g/m <sup>2</sup>	
	<b>SCHÖNOX® PROTECT Safety adhesive for the highest loads</b>	TKB A1	360 g/m <sup>2</sup>	Suitable for damp rooms
<b>Design floor 3.0</b>				
	<b>SikaBond®-151 Elastic parquet adhesive</b>	TKB B6	approx. 850 g/m <sup>2</sup>	

Dureco 12 mm	SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive	TKB B6	approx. 650 g/m <sup>2</sup>	
-----------------	--	--------	------------------------------	--

1

26.04.2023

BUILDING TRUST



## | Sika ADHESIVE RECOMMENDATION - ter Hürne

Covering/ Collection	Adhesive	Applicator/ toothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
Real wood floor				
Hywood real wood hybrid flooring wideplank	SikaBond®-151 Elastic parquet adhesive	TKB B11	approx. 800 g/m <sup>2</sup>	
	SikaBond®-54 Parquet Easy to apply, elastic parquet adhesive	TKB B11	approx. 800 g/m <sup>2</sup>	

### Cleaning

Accessories				
	Sika® PowerClean Moist Cleaning Wipes			for removing adhesive residues (in the uncured state)

Unless otherwise stated, all adhesives fulfil the requirements EC1 PLUS according to GEV.

Please observe the technical information in our product data sheets, the installation instructions of the flooring manufacturer, the relevant regulations, guidelines and data sheets. In case of doubt, we recommend a practical test and/or consultation with Sika Product Service Tel. 02547/910-325. Further information is available on the Internet at [www.sika.de](http://www.sika.de) or at [www.terhuerne.de](http://www.terhuerne.de)

