

PREMIUM CARE OIL NATURE

GB Deeply effective care-oil based on vegetable oils and carnauba wax. Refreshes dull, especially heavily used and intensively cleaned oiled surfaces. Enhances the wood grain. Good penetration properties and high filling capacity. Satin-matt visual effect. New recipe with higher solids content, lower odour and free of labelling obligation.

Application: Before application clean the floor well. Remove any care product layers by stripcleaning. Remove any stains before oiling and/or remove light scratches carefully with fine sandpaper. Shake up well before use, take off a skin if one has formed. Apply Premium Care Oil onto the floor thinly and evenly with a fluff-free cloth. After allowing it to soak in for 15 minutes, polish out the oil film completely, removing any surplus. We recommend using a monodisc-machine (e.g. Dr. Schutz SRP1) with a white pad. After polishing the floor should have a uniformly satin-matt appearance. In the case of serious damage to the surface to which the care product is applied, or when the absorbency of the parts in question is high, a further application may be necessary after the oil has dried. **Consumption:** 10-20 g/sq.m, depending on absorbency of the floor.

Drying time: Can be walked on carefully and worked on again after approx. 6 hours (at 23 °C, 50% relative air humidity with ventilation). The surface should not be wet-mopped in the first 7 days. After 10 days at the earliest carpets can be laid on the floor. **Storage:** Store in a cool, dry place in the closed original canister. Keeps for at least 24 months in unopened original canister from the date of manufacture. Keep locked up and out of the reach of children. **Contains substances:** vegetable oils, alkyd resin, carnauba wax, aliphatic hydrocarbons, drying agents free of lead and cobalt, additives. ADR: not a dangerous good as defined by transport regulations. CLP: no obligation to be labelled as hazardous.

Warning! Danger of spontaneous combustion of working materials moistened with oil, e.g. cloths, pads, sanding dust, etc. Therefore allow working materials to dry openly spread out and only dispose of them when they are completely dried. Or soak them in water and shut them in an airtight metal container to dispose of them in a fire-safe way. The oil itself is not self-combusting. Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using. Please also pay attention to our current Product Information and Safety Data Sheets at www.dr-schutz.com.

1L

For further information:

www.dr-schutz.com • info@dr-schutz.com

www.terhuerne.com