

# I SCHÖNOX ADHESIVE RECOMMENDATION - ter Hürne



## Substrate preparation

Substrates (for example)	Mastic asphalt according to DIN EN 13813 (AS)	Cement screed according to DIN EN 13813 (CT)	Calcium sulphate levelling screed or calcium sulphate flowing screed in accordance with DIN EN 13813(CA/CAF)	Dry screeds
Primers (for example)	SCHÖNOX SHP (Not applicable with sufficient sanding)  SCHÖNOX® HP RAPID (plasticiser barrier for direct bonding)	SCHÖNOX VD		
Levelling compounds (for example)	SCHÖNOX HS 10 SCHÖNOX HS 10 F SCHÖNOX HS 50			SCHÖNOX HS 10

## Covering bonding

Covering/ Collection	Adhesive	Applicator/ tothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
<b>Parquet flooring</b>				Field of application
<b>3-layer parquet</b>	<b>SCHÖNOX® PARQUET 250</b> Water-free special adhesive for parquet	TKB B11	approx. 1050 g/m <sup>2</sup>	
	<b>SCHÖNOX® iLINE® 250</b> Shear-elastic parquet adhesive	iLINE APP	approx. 800 g/m <sup>2</sup>	
	<b>SCHÖNOX® PARQUET 400</b> Water-free adhesive for parquet	TKB B11	approx. 1000 g/m <sup>2</sup>	
<b>Design coverings</b>				
<b>Vinyl Pro</b> 2.5 mm dryback sheet	<b>SCHÖNOX® DUROCOLL</b> Fibre-reinforced single-sided dispersion adhesive	TKB A1	approx. 250 g/m <sup>2</sup>	Suitable for damp rooms
	<b>SCHÖNOX® PROTECT</b> Safety adhesive for the highest loads	TKB A1	approx. 360 g/m <sup>2</sup>	

	<b>SCHÖNOX® PU 900</b> Two-component polyurethane adhesive	TKB A2	approx. 500 g/m <sup>2</sup>	including critical substrates, e.g. damp rooms and areas with strong sunlight/temperature exposure
<b>Vinyl Perform</b> 6 mm multilayer rigid and cork backing	<b>SCHÖNOX® PARQUET 250</b> Water-free special adhesive for parquet	TKB B6	approx. 850 g/m <sup>2</sup>	
	<b>SCHÖNOX® iLINE® 250</b> Shear-elastic parquet adhesive	iLINE APP	approx. 800 g/m <sup>2</sup>	

## I SCHÖNOX ADHESIVE RECOMMENDATION - ter Hürne



Covering/ Collection	Adhesive	Applicator/ toothing according to TKB	approx. consumption/m <sup>2</sup>	Remarks
<b>HDC Dryback 2.5 mm</b>	<b>SCHÖNOX® PROTECT</b> Safety adhesive for the highest loads	TKB A2	300 g/m <sup>2</sup>	Suitable for damp rooms
	<b>SCHÖNOX® DUROCOLL</b> Fibre-reinforced single-sided dispersion adhesive	TKB A1	360 g/m <sup>2</sup>	
<b>Design floor 3.0</b>				
<b>Dureco</b> 12 mm	<b>SCHÖNOX® PARQUET 250</b> Water-free special adhesive for parquet	TKB B6	approx. 850 g/m <sup>2</sup>	Only for privately used damp rooms
	<b>SCHÖNOX® PARQUET 54</b> Consumption-optimised, elastic, water-free special adhesive for parquet flooring	TKB B6	approx. 650 g/m <sup>2</sup>	e.g. critical substrates, e.g. damp rooms
<b>Real wood floor</b>				
<b>Hywood real wood hybrid flooring wideplank</b>	<b>SCHÖNOX® PARQUET 250</b> Water-free special adhesive for parquet	TKB B11	approx. 1050 g/m <sup>2</sup>	
	<b>SCHÖNOX® PARQUET 54</b> Consumption-optimised, elastic, water-free special adhesive for parquet flooring	TKB B 11	approx. 800 g/m <sup>2</sup>	

### Cleaning

Accessories				
	<b>SCHÖNOX® FIX CLEAN</b> Moist cellulose cleaning cloths			For easy removal of adhesive residues. Especially for contamination with uncured adhesive residues.

Unless otherwise stated, all adhesives fulfil the requirements EC1 PLUS according to GEV.

Please observe the technical information in our product data sheets, the installation instructions of the flooring manufacturer, the relevant regulations, guidelines and data sheets. In case of doubt, we recommend a practical test and/or consultation with SCHÖNOX Product Service Tel. 02547/910-325. Further information is available on the Internet at [www.schoenox.de](http://www.schoenox.de) or at [www.terhuerne.de](http://www.terhuerne.de)