



















Product details		Laminate Floor		
Dimension:		1285 x 192 x 7 mm	1285 x 192 x 8 mm	1288 x 195 x 8 mm
Groove:		without joint / V-groove 4-sided (4V)	without joint	V-groove 4-sided (4V)
Profile:		ClickTec	ClickTec	SmartConnect
packaging	package:	10 pieces per pack (ca. 2,467 m ²)	9 pieces per pack (ca. 2,22 m ²)	9 pieces per pack (ca. 2,26 m ²)
	pallet:	40 packs per pallet (ca. 98,68 m ²)	40 packs per pallet (ca. 88,8 m ²)	52 packs per pallet (ca. 117,52 m ²)
Weight	package:	ca. 14,8 kg	ca. 15,5 kg	ca. 15,0 kg
	pallet:	ca. 607,2 kg	ca. 635 kg	ca. 820 kg
tolerances: requirements EN 13329				
Flatness of element, f [%]	≤ 0,50 / ≤ 1,00 (lengthwise) ≤ 0,15 / ≤ 0,20 (wide)	Gap opening between elements, o [mm]		≤ 0,15 (average) ≤ 0,20 (single value)
High difference between elements, h [mm]	≤ 0,10 (average) ≤ 0,15 (single value)	Thickness of the elements, t [mm]		≤ 0,50
Squareness, q [mm]	≤ 0,20	Length of the surface layer, l [mm]		± 0,50 mm
Straightness, s [mm/m]	≤ 0,30	Width of the surface layer, w [mm]		± 0,10 mm (average) ≤ 0,20 mm (single value)
Decor deviation [mm]	± 2 mm			
Product construction				
 <ul style="list-style-type: none"> 1) Protective top layer 2) Decor layer 3) Baseboard 4) Backing Layer 				
Warranty (according to our separate terms of warranty)	15 years for domestic use 5 years for commercial use	Note		
      				
product properties				
		test standard	evaluation	
	Usage class Heavy domestic use	EN 13329	23	
	Usage class Moderate commercial use	EN 13329	31 valid for 7 mm thickness	
	Usage class Moderate commercial use	EN 13329	32 valid for 8 mm thickness	
	Abrasion resistance	EN 13329	IP ≥ 2000 turns (AC 3) for 7 mm thickness IP ≥ 4000 turns (AC 4) for 8 mm thickness	
	Reaction to fire	EN 13501-1	C(f) s1 flame retardant	
	Formaldehyde	EN 16516	E1	
	Light fastness	EN 13329	Blue wool scale ≥ 6 Grey scale ≥ 4	
	Slide resistance	EN 13893	The requirements are in compliance with DIN EN 14041 (my ≥ 0,3)	
	Elektrostatic behaviour	EN 1815	not antistatic	
	Imprint after constant loading	EN 13329	≤ 0,05 mm	
	Resistance to chair castors	EN 13329	no visible changes or impact as defined by (Typ W) EN 425:2002	
	Thermal resistance	EN 12667	0,062 (m ² K)/W ± 15%	
	Underfloor heating- hot water and electrical	EN 1264-2	Suitable with a maximum surface temperature of 27°. Electric panel heating with soft heating technology and temperature control unit are suitable as well.	
	Stain resistance	EN 13329	Group 1 + 2 = degree 5 Group 3 = degree 4	
	Impact stress resistance	EN 13329	small ball ≥ 10 mm · big ball ≥ 500 mm for 7 mm thickness small ball ≥ 35 mm · big ball ≥ 750 mm for 8 mm thickness	
changed by:	ter Hürne	date:	Feb. 24	update