

# MAPEI ADHESIVE RECOMMENDATION



## Flooring installation

Covering	Adhesives	Toothing	Consumption
Multi-layer parquet <ul style="list-style-type: none"> <li>- Parquet with HDF core</li> <li>- Parquet with spruce core</li> <li>- Base 59</li> </ul>	<b>ULTRABOND ECO S968 1K</b> <b>ULTRABOND ECO S958 1K</b> <b>ULTRABOND ECO S948 1K</b> <b>ULTRABOND ECO S940 1K</b>	TKB B11	approx. 1,000 g/m <sup>2</sup>
Hybrid wood flooring <ul style="list-style-type: none"> <li>- Hywood</li> </ul>	<b>ULTRABOND ECO S968 1K</b> <b>ULTRABOND ECO S958 1K</b> <b>ULTRABOND ECO S948 1K</b> <b>ULTRABOND ECO S940 1K</b>	TKB B3	approx. 800 g/m <sup>2</sup>
Soya Design vinyl flooring <ul style="list-style-type: none"> <li>- Pro</li> </ul>	<b>ULTRABOND ECO 4 LVT</b> <b>ULTRABOND ECO V4SP</b>  <b>ULTRABOND ECO MS 4 LVT WALL&amp;FLOOR</b>	TKB A1 / A2  TKB A4	approx. 250 g/m <sup>2</sup>  approx. 200 g/m <sup>2</sup>
Soya Design vinyl flooring <ul style="list-style-type: none"> <li>- Perform</li> </ul>	<b>ULTRABOND ECO S968 1K</b> <b>ULTRABOND ECO S958 1K</b> <b>ULTRABOND ECO S948 1K</b> <b>ULTRABOND ECO S940 1K</b>	TKB B3	approx. 800 g/m <sup>2</sup>

The products mentioned describe the application in abbreviated form. The technical data sheets for the products and the currently applicable standards and guidelines must be observed. If structures other than those described here are used, these are only possible after approval and consultation with the MAPEI GmbH application technology department. This recommendation is only valid for MAPEI GmbH in Germany. For use in other countries, please contact the respective MAPEI company or MAPEI SpA at [www.mapei.it](http://www.mapei.it).

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at [www.mapei.it](http://www.mapei.it).

Covering	Adhesives	Toothings	Consumption
Friends by ter Hürne vinyl flooring - Dryback	<b>ULTRABOND ECO 4 LVT</b> <b>ULTRABOND ECO V4SP</b>	TKB A1 / A2	approx. 250 g/m <sup>2</sup>
	<b>ULTRABOND ECO MS 4 LVT WALL&amp;FLOOR</b>	TKB A4	approx. 200 g/m <sup>2</sup>
Design wood flooring - Dureco	<b>ULTRABOND ECO S968 1K</b> <b>ULTRABOND ECO S958 1K</b> <b>ULTRABOND ECO S948 1K</b> <b>ULTRABOND ECO S940 1K</b>	TKB B3 / B11	approx. 1,000 g/m <sup>2</sup>

### Substrate preparation

Filling compound	<b>ULTRAPLAN XTRA</b>	<b>ULTRAPLAN XTRA</b>	<b>PLANITEX FAST</b>	<b>ULTRAPLAN XTRA</b>	<b>PLANITEX FAST</b>
Primer	<b>PRIMER MF</b>	<b>ECO PRIM T PLUS</b> Diluted 1:3 with water	<b>ECO PRIM T PLUS</b> Diluted 1:2 with water	<b>ECO PRIM GRIP PLUS</b>	<b>ECO PRIM T PLUS</b> Diluted 1:1 with water
Underground	Concrete	Cement screed	Calcium sulphate screed	Existing Ceramic tiles	Mastic asphalt

The products mentioned describe the application in abbreviated form. The technical data sheets for the products and the currently applicable standards and guidelines must be observed. If structures other than those described here are used, these are only possible after approval and consultation with the MAPEI GmbH application technology department. This recommendation is only valid for MAPEI GmbH in Germany. For use in other countries, please contact the respective MAPEI company or MAPEI SpA at [www.mapei.it](http://www.mapei.it).

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at [www.mapei.it](http://www.mapei.it).