

MAPEI ADHESIVE RECOMMENDATION



Flooring installation

Covering	Adhesives	Toothings	Consumption
Multi-layer parquet - Parquet with HDF core - Parquet with spruce core - Base 59	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B11	approx. 1,000 g/m ²
Hybrid wood flooring - Hywood	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3	approx. 800 g/m ²
Soya Design vinyl flooring - Pro	ULTRABOND ECO 4 LVT ULTRABOND ECO V4SP ULTRABOND ECO MS 4 LVT WALL&FLOOR	TKB A1 / A2 TKB A4	approx. 250 g/m ² approx. 200 g/m ²
Soya Design vinyl flooring - Perform	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3	approx. 800 g/m ²

The products mentioned describe the application in abbreviated form. The technical data sheets for the products and the currently applicable standards and guidelines must be observed. If structures other than those described here are used, these are only possible after approval and consultation with the MAPEI GmbH application technology department. This recommendation is only valid for MAPEI GmbH in Germany. For use in other countries, please contact the respective MAPEI company or MAPEI SpA at www.mapei.it.

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at www.mapei.it.

Covering	Adhesives	Toothings	Consumption
Friends by ter Hürne vinyl flooring - Dryback	ULTRABOND ECO 4 LVT ULTRABOND ECO V4SP	TKB A1 / A2	approx. 250 g/m ²
	ULTRABOND ECO MS 4 LVT WALL&FLOOR	TKB A4	approx. 200 g/m ²
Design wood flooring - Dureco	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3 / B11	approx. 1,000 g/m ²

Substrate preparation

Filling compound	ULTRAPLAN XTRA	ULTRAPLAN XTRA	PLANITEX FAST	ULTRAPLAN XTRA	PLANITEX FAST
Primer	PRIMER MF	ECO PRIM T PLUS Diluted 1:3 with water	ECO PRIM T PLUS Diluted 1:2 with water	ECO PRIM GRIP PLUS	ECO PRIM T PLUS Diluted 1:1 with water
Underground	Concrete	Cement screed	Calcium sulphate screed	Existing Ceramic tiles	Mastic asphalt

The products mentioned describe the application in abbreviated form. The technical data sheets for the products and the currently applicable standards and guidelines must be observed. If structures other than those described here are used, these are only possible after approval and consultation with the MAPEI GmbH application technology department. This recommendation is only valid for MAPEI GmbH in Germany. For use in other countries, please contact the respective MAPEI company or MAPEI SpA at www.mapei.it.

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at www.mapei.it.

MAPEI KLEBSTOFFEMPFEHLUNG



Belagsverlegung

Belag	Klebstoffe	Zahnung	Verbrauch
Mehrschichtparkett - Parkett mit HDF-Träger - Parkett mit Fichte-Träger - Base 59	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B11	ca. 1.000 g/m ²
Hybridholzboden - Hywood	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3	ca. 800 g/m ²
Soya Design Vinylboden - Pro	ULTRABOND ECO 4 LVT ULTRABOND ECO V4SP	TKB A1 / A2	ca. 250 g/m ²
	ULTRABOND ECO MS 4 LVT WALL&FLOOR	TKB A4	ca. 200 g/m ²
Soya Design Vinylboden - Perform	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3	ca. 800 g/m ²

Die erwähnten Produkte beschreiben die Anwendung in verkürzter Form. Zu beachten sind die Technischen Merkblätter der Produkte sowie die aktuell gültigen Normen und Richtlinien. Sollten andere als hier dargestellte Aufbauten eingesetzt werden, sind diese nur nach Freigabe und Rücksprache mit der Anwendungstechnik der MAPEI GmbH möglich. Diese Empfehlung ist nur gültig für die MAPEI GmbH in Deutschland. Bei Verwendung in anderen Ländern wenden Sie sich bitte an die jeweilige MAPEI-Gesellschaft oder an MAPEI SpA unter www.mapei.it.

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at www.mapei.it.

Belag	Klebstoffe	Zahnung	Verbrauch
Friends by ter Hürne Vinylboden - Dryback	ULTRABOND ECO 4 LVT ULTRABOND ECO V4SP	TKB A1 / A2	ca. 250 g/m ²
	ULTRABOND ECO MS 4 LVT WALL&FLOOR	TKB A4	ca. 200 g/m ²
Designholzboden - Dureco	ULTRABOND ECO S968 1K ULTRABOND ECO S958 1K ULTRABOND ECO S948 1K ULTRABOND ECO S940 1K	TKB B3 / B11	ca. 1.000 g/m ²

Untergrundvorbereitung

Spachtelmasse	ULTRAPLAN XTRA	ULTRAPLAN XTRA	PLANITEX FAST	ULTRAPLAN XTRA	PLANITEX FAST
Grundierung	PRIMER MF	ECO PRIM T PLUS 1:3 mit Wasser verdünnt	ECO PRIM T PLUS 1:2 mit Wasser verdünnt	ECO PRIM GRIP PLUS	ECO PRIM T PLUS 1:1 mit Wasser verdünnt
Untergrund	Beton	Zementestrich	Calciumsulfat-estrich	Bestehende keramische Fliesen	Gussasphalt

Die erwähnten Produkte beschreiben die Anwendung in verkürzter Form. Zu beachten sind die Technischen Merkblätter der Produkte sowie die aktuell gültigen Normen und Richtlinien. Sollten andere als hier dargestellte Aufbauten eingesetzt werden, sind diese nur nach Freigabe und Rücksprache mit der Anwendungstechnik der MAPEI GmbH möglich. Diese Empfehlung ist nur gültig für die MAPEI GmbH in Deutschland. Bei Verwendung in anderen Ländern wenden Sie sich bitte an die jeweilige MAPEI-Gesellschaft oder an MAPEI SpA unter www.mapei.it.

Please note: This recommendation is valid only for the German market. For recommendations in other countries, please contact your local MAPEI subsidiary or MAPEI HQ at www.mapei.it.