

Product details		UniqueDesign panels		
		Decor Edition		Linear Edition
Format		1300 x 250 x 12 mm	2600 x 250 x 12 mm	2600 x 148 x 12
Deckmaß		1295 x 237,2 x 12 mm	2595 x 237,2 x 12 mm	2600 x 135 x 12 mm
Bevel		visible joint of 0 mm		-
Profile		Tongue and groove for clip fixing		
Type of installation		MDF (720 +/-30 kg/m <sup>3</sup> )		
Gloss level		mat / silk mat / glossy		mat / silk mat
Packaging	Pack:	4 pieces per pack (approx. 1,3 m <sup>2</sup> )	4 pieces per pack (approx. 2,6 m <sup>2</sup> )	4 pieces per pack (approx. 1,539 m <sup>2</sup> )
	Pallet:	30 packs per pallet (approx. 39 m <sup>2</sup> )	30 packs per pallet (approx. 78 m <sup>2</sup> )	50 packs per pallet (approx. 76,96 m <sup>2</sup> )
Weight	Pack:	11,1 kg	22,15 kg	10,88 kg
	Pallet:	358 kg	714 kg	594 kg
<b>Product construction:</b>  1 Textured coating 2 Decor paper 3 Swell-reduced MDF baseboard (E1 quality) 4 Tongue and groove profile for clip fixing				
<b>Tolerances:</b>				
Height difference, h [mm]		≤ 0,4 mm	Gap opening, o [mm]	≤ 0,3 mm
Squareness, q [mm]		0,2%; max. 0,3 mm	Thickness, t [mm]	± 0,5 mm
Straightness, s [mm/m]		1 mm	Length, l [mm]	± 2 mm
Dimensional change due to air humidity fluctuation [%]		≤ 0,25	Width, w [mm]	± 1 mm
<b>Certificates</b>				
				
<b>Usage / surface properties (test standard)</b>				
			<b>Test standard</b>	<b>Evaluation</b>
		Reaction to fire	EN 13501	D-s2, d0
		Formaldehyde emission (E1 = 0,1 ppm)	EN 717-1	E1
		PCP-content	EN13986-5, 18 + A1	≤ 5
		Suitability of recessed lights		Heat-resistant up to 110 °C. Suitable for installation of tested recessed lights with MM- labeling
		Suitability for humid rooms		Suitable with adequate ventilation and no direct contact with water
		Fixing		Clip No. 2
		Disposal		Private disposal with regular household waste / bulk waste possible
Changed by	ter Hürne	Date:	Jul. 24	Update: <a href="http://www.terhuerne.com">http://www.terhuerne.com</a>